PAV/PAVO 2-WAY & 3-WAY AIR-PILOTED VALVES

PAV-PAVO Air-Piloted Valves

These Normally-Open or Normally-Closed 2-way and 3-way valves incorporate an integral pilot actuator that provides a compact assembly and simple installation. The internal valving is identical to the MAV-2/3 or MAVO-2/3.

Medium: Air, Water or Oil

Input Pressure: PAV-2/3: 300 psig; PAVO-2/3:150 psig max.

Air Pilot Pressure: 15 psig min.


Air Flow: PAV-2/3: 4.0 scfm @ 50 psig; 6.8 scfm @ 100 psig; PAVO-2/3: 6.8 scfm @ 50 psig; 11.6 scfm @ 100 psig

Mounting: 5/8-32 thread or #4 screw. Nut and lockwasher may be ordered

separately. Part Number: PAV-MH

Materials: Brass body, Nitrile seals, stainless steel stem and spring

Foot Bracket: FB-1791



· Air-piloted valves are ideal for remote and miniature applications where you need higher air flow and/or lower power.



Normally-Closed Poppet Valves



(PAV-2P shown)

Port(s)	2-Way	3-Way	
#10-32	PAV-2	PAV-3	
1/8" NPT	PAV-2P	PAV-3P	


Normally-Open Spool Valves




(PAVO-2 shown)

Port(s)	2-Way	3-Way	
#10-32	PAVO-2	PAVO-3	
1/8" NPT	PAVO-2P	PAVO-3P	







solutions

If you need a product that fits your application perfectly, Clippard has the capability to design or modify one of its products to suit your exact needs. We understand that a standard catalog product may be close but not be exactly what you need. Let us know YOUR Need, and we will help to find YOUR Solution!

Specials!

Clippard has been and still is a pioneer in miniature pneumatics. This cartridge 2-way valve is small and packs a lot of flow into a very tight package. If you don't see what you need in this section, just call us!